

# AUTOMATIC TAPING MACHINE **COM**® JD SERIES

DESK TOP TYPE FOR PAPER TAPE OR FILM TAPE

Highly efficient, secure banding of a wide variety of works.

## ■ FEATURES

- Banding can be several times more efficient than that of hand taping.
- Patented mechanism for smooth tape feeding and taping.
- Heat adhesion system ensures very tight banding.
- Items to be taped are free from any stain as no subsidiary materials (adhesives, hot melt etc.) are used.
- Single winding design features tape cost saving.
- Desk-top design features space saving and light weight for easy setting at any place.



JD-150F



JD-240

## ■ CAPABILITY

Model	Product size	Speed
JD-150F	Max. (width 150mm, height 140mm) Min. (width 30mm, height 5mm)	25 cycles/minute (approx.)
JD-240	Max. (width 240mm, height 170mm) Min. (width 30mm, height 5mm)	

## ■ MACHINE SPECIFICATIONS

Model	Tape width (mm)	Width	Height	Depth	Table height	Power supply	Allowable tape
JD-150F-20/30	425mm	400mm	287mm	230mm	115V/220V/230V/240V 50Hz/60Hz	Film tapes	
JD-240-20/25/30						Paper tapes	
JD-150F-40	435mm	300mm	230mm	115V/220V/230V/240V 50Hz/60Hz	115V/220V/230V/240V 50Hz/60Hz	Film tapes	
JD-240-40						Paper tapes	

## ■ COM TAPE SPECIFICATIONS

Type	Width	Thickness
Paper	20mm/25mm/30mm/40mm	70g (brown)/80g (white)
Film	20mm/30mm/40mm	80 micron/100 micron/MAGIC CUT 110 micron

● Note: Use only the tapes supplied or approved by the machine manufacturer.

● Other than tapes mentioned above; color tapes, printed tapes, etc., can also be made to order.

● Specifications subject to change without notice.

**COM is Communication.**

**TAIYO SEIKI CO., LTD.**

Head Office: 4-3-7, Hino, Daitoh, Osaka, 574-0062, Japan.

Phone: 81-72-873-3739 Fax: 81-72-875-4324

U R L : <http://www.com-machine.co.jp>

E-mail: [taiyo@com-machine.co.jp](mailto:taiyo@com-machine.co.jp)